

# Mailinglist – php example code – part 5 – unsubscribe by e-mail for users

Article focus on improvement mailinglist app for enabling access for common users only on by e-mail unsubscription without ability to see list of all subscribed users.

## Goal of unsubscribe by user app extension


For further security hardening (not main improvement but first partialy update) we separate page for unsubscribing for admin (somebody who knows name of that page – no improvement in this way is done) and for unsubscribing for common user.

Users cannot see list of all subscribers names and email. But there is no way for refering any changes in the table. For better user experience, we expanded messaging output for information about:

- that e-mail was found in database table – select query search database for appropriate e-mail
- that e-mail was succesfully deleted from databse

- or warning message that e-mail was not found (user with this e-mail is not subscribed for mailing)

Frontend of the page after inserting wrong e-mail looks like this



e-mail is not in subscribers list

or succesfull e-mail removed output

Mailinglist app v 1.0 - unsubscribing for user

RETURN TO HOME ->

Subscriber with e-mail: test@test.com was found in database for deletion.

Subscriber with e-mail: test@test.com has been succesfully removed from mailinglist.



e-mail to unsubscribe:

test@test.com

UNSUBSCRIBE

RESET FORM

*Your e-mail:* test@test.com  
has been succesfully removed from mailinglist.

Visit us on CDesigner.eu

e-mail was found and removed from list

## Main logic of script

Next code snippet contains logic for finding appropriate-mail and show message about succesfull search. Next deleting selected e-mail from subscription list.

```

<?php
    // two variables for message and styling of the message with bootstrap
    require_once('appvars.php'); // including variables for database

    $msg = "";
    $msgClass = "";
    $msg_about_contains_email = "";
    $msgClass_email = "";

    // default values of auxiliary variables
    $email = "";

    $is_removed = false; //before hitting submit button no result is available
    $is_present = false; // email is not in the table – default before selecting against user submitted email for deletion

    if(filter_has_var(INPUT_POST, 'submit')){
        // Data obtained from $_postmessage are assigned to local variables
        $email = htmlspecialchars($_POST['email']);

        // Controll if all required fields was written
        if(!empty($email) ) {
            // If check passed – all needed fields are written
            if(filter_var($email, FILTER_VALIDATE_EMAIL) === false){
                // E-mail is not valid
                $msg = 'Please use a valid email';
                $msgClass = 'alert-danger';
            } else {

```

```

// E-mail is valid - now delete row with matching e-mail

// make database connection
$dbc = mysqli_connect(DB_HOST, DB_USER, DB
_PW, DB_NAME);

// Check connection
if($dbc === false){
    die(„ERROR: Could not connect to d
atabase. “ . mysqli_connect_error());
}

// get info if appropriate e-
mail is in mailinglist
// create SELECT query
$sql = „SELECT email FROM mailinglist
WHERE email = „.$email““;

if(($row[,email'] = mysqli_fetch_array
($result = mysqli_query($dbc, $sql))) != ,,){

    $msg_about_contains_email = ,Subsc
riber
with
mail: ,.$email. , was found in database for deletion.‘;
    $msgClass_email = ,alert-success‘;
    $is_present = true;

// create DELETE query
$sql = „DELETE FROM mailinglist WH
ERE email = „.$email““ LIMIT 1“;

if(mysqli_query($dbc, $sql)){

    $msg = ,Subscriber with e-
mail: ,.$email. , has been succesfully removed from mailinglis
t.‘;

    $msgClass = ,alert-success‘;
    $is_removed = true;

```

```

};

} else{
    $msg_about_contains_email = ,Subscriber
    with e-mail: ,.$email. , was not found in database for deletion. Probably was not subscribed for mailing.';
    $msgClass_email = ,alert-warning,;
    $msg = „ERROR: Could not able to execute $sql. “ . mysqli_error($dbc);
    $msgClass = ,alert-danger';
    $is_present = false;
};

// end connection
mysqli_close($dbc);
};

} else {
    // Failed – if not all fields are fullfilled
    $msg = ,Please fill in all fields';
    $msgClass = ,alert-danger'; // bootstrap format for allert message with red color
};
};

// if reset button clicked
if(filter_has_var(INPUT_POST, ,reset')){
    $msg = “;
    $msgClass = “; // bootstrap format for allert message with red color
    $subject =“;
    $email =“;
    $msg_about_contains_email = “;
};
};

```

?>

Full code of page `usrunsub.php` can be obtained from github here.